

What is claimed is:

1. A method for encoding and transmitting still picture images comprising:

receiving video frames at an input frame rate;

capturing ones of said video frames at a still picture capture rate which is less than the input frame rate;

providing the captured video frames to a video compressor at the input frame rate, wherein an already captured video frame is repeatedly provided to said video compressor at the input frame rate until a new frame is captured; and

transmitting the captured video frames after compression by said video compressor at a still picture repetition rate that is no less than said capture rate.

2. A method in accordance with claim 1 wherein said input frame rate is about 30 frames per second.

3. A method in accordance with claim 1 wherein said still picture repetition rate is within a range of about 1/30 to two frames¹ per second.

09737153-121400

4. A method in accordance with claim 3 wherein said still picture repetition rate is no greater than about 1/15 frames per second.

5. A method in accordance with claim 4 wherein said input frame rate is about 30 frames per second.

6. A method in accordance with claim 1 wherein said video compressor compresses all of the captured frames as I-frames.

7. A method in accordance with claim 1 wherein:
compressed captured video frames to be
transmitted are gated from the video compressor to a
buffer in accordance with the frame repetition rate;
and

the frames are provided as output from said
buffer for transmission at the frame repetition rate.

8. A method in accordance with claim 7 wherein
only selected ones of the compressed captured video
frames are gated into said buffer for transmission.

09737152 121400

9. A method in accordance with claim 1 wherein the compressed, captured video frames are transmitted at a bit rate on the order of 100 Kbps to 200 Kbps.

10. Apparatus for encoding and transmitting still picture images comprising:

a selector adapted to receive video frames at an input frame rate and capture a subset of the video frames at a still picture capture rate which is less than the input frame rate;

a video compressor coupled to receive and compress the captured video frames at the input frame rate, wherein an already captured video frame is repeatedly provided to said video compressor at the input frame rate until a new frame is captured; and

a buffer coupled to receive the captured video frames after compression by said video compressor for subsequent transmission at a still picture repetition rate that is no less than said capture rate.

11. Apparatus in accordance with claim 10, further comprising:

a current frame buffer coupled to store the video frames prior to capture thereof by said selector; and

004515 1.2.14.00

14. Apparatus in accordance with claim 10 further comprising a gate between said video compressor and said buffer, said gate being adapted to provide selected ones of the compressed video frames to the buffer in accordance with said still picture repetition rate.

compressing video frames at an input frame rate;

the second captured video frame can be repeatedly provided for transmission from said second memory at the still picture repetition rate while said first memory awaits storage of a subsequent captured video frame.

17. A method in accordance with claim 15 wherein said input frame rate is about 30 frames per second.

18. A method in accordance with claim 15 wherein said still picture repetition rate is within a range of about 1/30 to two frames per second.

19. A method in accordance with claim 18 wherein said still picture repetition rate is no less than about 1/15 frames per second.

20. A method in accordance with claim 19 wherein said input frame rate is about 30 frames per second.

21. A method in accordance with claim 15 wherein said video compressor compresses all of the captured frames as I-frames.

22. A method in accordance with claim 15 wherein the compressed, captured video frames are transmitted at a bit rate on the order of 100 Kbps to 200 Kbps.

23. Apparatus for encoding and transmitting still picture images comprising:

004431 25760

said first memory being responsive to a first write enable control input to store a first compressed video frame in accordance with said still picture capture rate, and being responsive to a first read enable control input to provide the first compressed

video frame as output in accordance with said still picture repetition rate; and

said second memory being responsive to a second write enable control input to store a second compressed video frame in accordance with said still picture capture rate, and being responsive to a second read enable control input to provide the second compressed video frame as output in accordance with said still picture repetition rate.

25. Apparatus in accordance with claim 24 wherein said write enable and read enable control inputs control said first memory to store a video frame while a previous video frame is being read from said second memory, and vice-versa.

26. Apparatus in accordance with claim 23 wherein said video compressor compresses all of the received frames as I-frames.

004450 25 12400